



Product Service

Attestation of Conformity

No. N8A 084752 0028 Rev. 00

Holder of Certificate: **München Energieprodukte GmbH**
Stethaimerstr. 32-34
84034 Landshut
GERMANY

Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062032201-00

Date, 2020-10-21

(Zhulin Zhang)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 084752 0028 Rev. 00

Model(s):

MSMDxxxM2-36, xxx =320 to 375 in step of 5;
 MSMDxxxM2-30, xxx =270 to 315 in step of 5;
 MSMDxxxM2-27, xxx =240 to 265 in step of 5;
 MSMDxxxM2-18, xxx =160 to 185 in step of 5;
 MSMDxxxM3-36, xxx =350 to 395 in step of 5;
 MSMDxxxM3-30, xxx =290 to 330 in step of 5;
 MSMDxxxM3-27, xxx =260 to 300 in step of 5;
 MSMDxxxM3-24, xxx =230 to 265 in step of 5;
 MSMDxxxM3-18, xxx =175 to 200 in step of 5;
 MSMDxxxM2-72, xxx =340 to 410 in step of 5;
 MSMDxxxM2-60, xxx =300 to 340 in step of 5;
 MSMDxxxM3-72, xxx =380 to 420 in step of 5;
 MSMDxxxM3-60, xxx =320 to 350 in step of 5;
 MSMDxxxM6-72, xxx =430 to 450 in step of 5;
 MSMDxxxM6-60, xxx =355 to 370 in step of 5;
 MSMxxxAS-36, xxx =190 to 210 in step of 5;
 MSMxxxAS-18, xxx =95 to 105 in step of 5;
 MSMCxxxAS-36, xxx =150 to 295 in step of 5;
 MSMCxxxAS-18, xxx =5 to 145 in step of 5;
 xxx is standing for rated output power at STC.

Parameters:

Construction:	Framed, with Junction box, Cable and connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute, No. 10 West Kaifa Road, Yangzhou 225009 Jiangsu, P. R. China.
Safety Class:	Class II
Max. system voltage:	1500V DC
Fire Safety Class:	Class C

Tested according to:

EN IEC 61730-1:2018
 EN IEC 61730-1:2018/AC:2018-06
 EN IEC 61730-2:2018
 EN IEC 61730-2:2018/AC:2018-06